

## DETECTING DEVICE FOR FLUORESCENT-LABELED MATERIAL

### Field of the Invention

[0001.] The present invention relates to a hand-held or bench-top fluorescence detector for fluorescent labeled material.

### Background of the Invention

[0002.] Fry stocking is a primary management strategy of the U.S. fish and wildlife Service and cooperating state fishery agencies for restoring populations of fish, for example, restoring Atlantic salmon, *Salmo salar*, to the New England states. In order to determine the effectiveness of this strategy in achieving management goals, identification of stocked fish is critical. Therefore, it would be useful to have a technique for marking larval (nonfeeding) fish with a readily recognizable tag or mark capable of being non-lethally detected in fry, parr, smolts, and returning adult fish.

[0003.] A variety of attempts have been made to mark salmonid fry by mechanical or chemical techniques. Unfortunately, none of these methods has been adequately refined or proven practical for marking large numbers of Atlantic salmon fry with a feature that can be non-lethally detected in subsequent life stages of the fish. Kaill et al. (1990) evaluated the use of half-length coded wire tags in emergent pink salmon *Oncorhynchus gorbuscha* and reported short-term retention rates of 93-100% and long-term retention rate estimates of 50-84%.

2025-03-28 14:38:00

[0004.] This technique was tested on Atlantic salmon larvae in 1994 by U.S. Fish and Wildlife biologists at the Northeast Fishery Center, Lamar, PA, but proved to be ineffective and impractical with this species due to the small size of fry (J.W. Fletcher, NEFC, personal communication). In general, chemical marks induced in fish from immersion in dyes or stains produce short-term marks that are detectable only for days, rather than for years. Injecting dyes and stains produces more durable marks, but the fish are subjected to greater stresses during handling and marking (Muncy et al., 1990). Immersion, injection, or feeding of fluorescent chemicals, such as oxytetracycline, can produce a mark on calcified fish tissues that is detectable under ultraviolet light or through fluorometric techniques (Muncy et al., 1990). Oxytetracycline has been used to mark teleost otoliths for subsequent age validation, but the fish must be sacrificed for mark determination. Wilson et al. (1987) reported that calcein, a compound that fluoresces green under long wave ultraviolet light, produced a detectable mark on otoliths of three species of estuarine fish after a two hour immersion in a calcein solution of 125 mg/L.

[0005.] Calcein chemically binds with calcium and shows a marked increase in fluorescence when complexed with alkaline earth metals (Wallach et al., 1959). Calcein has been used as an indicator to determine the calcium content of limestone and gypsum (Diehl and Ellingboe, 1956), for determining

submicrogram quantities of cadmium (Hefley and Jaselskis, 1974), as a stain for angiography (Oncel et al., 1990), and for fitting soft hydrophilic contact lenses (Refojo et al., 1972).

[0006.] Prior methods for detecting fluorescent-labeled organisms required use of a microscope outfitted with the proper filters for detecting fluorescing marks in fish or other biological materials. This created the problem of transporting an expensive, delicate microscope into outdoor and harsh environments, and required that individual specimens be placed onto the microscope stage for examination. Microscope stages are not intended for examination of whole, live specimens. Even specimens which could be partially examined via microscopy were subject to excessive manipulation and focusing time to attempt evaluation for the fluorescing mark. These procedures are prohibitory for efficiently evaluating large-sized specimens or large numbers of individuals while maintaining the life of live specimens if necessary.

[0007.] One conventional detector for incident light fluorescence is the AO Vertical Illuminator for Light Fluorescence microscopy, produced by Reichert Scientific Instruments, Buffalo, New York, which is based on microscopy. This conventional illuminator module comprises a tungsten halogen lamp or a mercury vapor lamp to provide a source of excitation energy, collector lens system and filed diaphragm

to efficiently control the beam, exciter filters to transmit selected wavelengths, dichroic beamsplitters to selectively reflect and subsequently transmit desirable wavelengths, and barrier filters to bar unwanted wavelengths. The dichroic element reflects excitation energy wavelengths up to a predetermined cutoff point. Longer wavelengths, as emitted by fluorescence energy, pass through the dichroic element and are not deflected from their paths. Excitation energy, which is beamed from the lamp through the exciter filter, is reflected by the dichroic element down through the microscope objective into the specimen. Fluorochromes within a specimen, excited by the energy beam from the objective, emit visible fluorescence energy which returns up through the microscope objective, dichroic element, and barrier filters to the microscope eyepiece or camera.

[0008.] Methods for monitoring using fluorescence include that shown in Rao et al., U.S. Patent No. 5,628,310. This method is for transdermal measurements of the fluorescence lifetime of an implanted element. This method, however, requires implantation of the fluorescent device.

[0009.] Krauthamer, in U.S. Patent No. 5,239, 998, discloses a method and apparatus for detecting fluorescence emitted at a remote situs, namely, tissue stained with a voltage-sensitive dye. This method and apparatus are designed to record the electrical activity of tissues stained with voltage-sensitive dyes rather than to detect marked tissues.

[0010.] Harte, in U.S. Patent No. 4,056,724, discloses a fluorometric system for detection of sample substances derived from biological fluid, or tissue targeted with fluorochromes. This apparatus requires that the sample substance be coated over a surface on a solid substrate, which means that it cannot be used to detect fluorescence in whole animals.

[0011.] Thus, there is a need for batch-marking small organisms such as fish and other animals, along with a need for practical, non-lethal field detection of the mark in order to differentiate between groups of organisms, such as hatchery-reared vs wild fish. There is a need for a portable device which can withstand the rigors of outdoor field work and be used to examine samples too large for standard microscopy.

#### **Summary of the Invention**

[0012.] It is an object of the present invention to overcome the aforesaid deficiencies in the prior art.

[0013.] It is another object of the present invention to provide a device for determining the presence or absence of a fluorescent marker in calcified biological tissues and other materials after exposure to a fluorochrome.

[0014.] It is a further object of the present invention to provide a device for use in the field to differentiate between marked and unmarked individuals without the aid of a microscope.

[0015.] According to the present invention, the proper

combination of light, light filters, and other lenses with the known properties of the fluorochrome chemical being detected results in visible detection of the chemical as it fluoresces a characteristic color after it becomes bound to calcified tissues of biological origin.

[0016.] For purposes of the present invention, any fluorochrome or fluorescing material which can be applied to a biological, natural, or synthetic material which is capable of being labeled such that fluorescence occurs can be detected with the device of the present invention. Filters and lenses in the device can be interchanged with other filters and lenses to detect specific fluorochromes or fluorescing material.

[0017.] A fluorochrome-marked sample is excited with the proper wattage and wavelength of light using an exciter or bandpass filter. This causes the sample to emit light of a slightly higher wavelength than that of excitation. A subsequent barrier filter of the proper configuration placed between the sample and the observer allows this longer wavelength to be observed as fluorescence. A beamsplitting mirror device may or may not be incorporated to deflect the light path and/or enhance fluorescence detection. This technique is particularly useful for viewing large biological specimens such as fish.

[0018.] The device of the present invention is particularly useful for samples in which microscopic examination is not

practical or desirable, e.g., because of the size of the sample to be examined, the physical nature of the location when detection must occur, or other limitations.

[0019.] In one embodiment of the invention, a set of eyeglasses made of the same glass used for the longpass barrier filter are worn by the operator to view the specimen from any vantage point as long as light from the detector strikes the specimen. This allows the operator greater freedom of movement and does not restrict the sample size.

#### **Brief Description of the Drawings**

[0020.] Figure 1 shows a hand-held fluorescence detection device for detecting visible fluorescence emitted from fluorescent-labeled samples.

[0021.] Figure 2 shows a bench-top fluorescence detection device for detecting visible fluorescence emitted from fluorescent-labeled samples.

[0022.] Figure 3 shows detection of a sample using eyeglasses having the same glass used for the long pass barrier filter.

[0023.] Figure 4 shows a hand-held calcein detector.

[0024.] Figure 5 shows a cutaway view of a fluorochrome detector.

#### **Detailed Description of the Invention**

[0025.] The present invention permits gross examination of fish or other biological or non-biological material for the presence or absence of a fluorochrome dye, which is manifested

as visible fluorescence. The presence of fluorescence from the organism or material being examined is a verification of past marking of the sample.

### Apparatus

[0026.] Referring to Figure 1, light generated by a hand-held illuminator (AC or battery-powered) 1 passes through an exciter or bandpass filter 3, allowing only a first predetermined wavelength or range of wavelengths of light to pass through. This filter is held in place by a mount 2 and a lens holder 4. The light beam strikes the beamsplitter 10 and is directed down toward a specimen 12, which is excited by the incident light. The beamsplitter 10 is held to the light source by means of adapter 5, and an extension tube 6 provides mechanical clearance. If the specimen contains sufficient fluorochrome, the specimen will emit light of a slightly longer wavelength than that of the incident light. This emitted light will be reflected upwards from the specimen and through the beamsplitter 10 upwardly towards the line of sight. From the beamsplitter, the emitted light will then pass through the barrier or longpass filter 8 where only light greater than a second predetermined wavelength, which is longer than the first predetermined wavelength, will be allowed to pass to the eye of the observer (line of sight 13). Alternatively, as shown in Figure 3, an operator wearing eyeglasses 14 equipped with the same lenses as in the barrier or long pass filter 8 can view the emitted fluorescence from



any vantage point and is not limited by the geometry of the hand-held device. The presence of fluorochrome in the specimen will cause a visible fluorescence to occur. The achromatic lens 7 will provide some magnification of the fluorescing object to the viewer. A barrier filter 8 and achromatic lens 7 are held to the beam splitter by a threaded lens holder 9.

[0027.] Where the indicator is calcein, the first predetermined wavelength is approximately 490 nm, and the second predetermined wavelength is approximately 520 nm. The emitted fluorescence is green. However, the first and second predetermined wavelengths can be adjusted by substituting specific filters and beamsplitters depending upon the fluorochrome used.

[0028.] There is no preferred difference between excitation and emission wavelengths. For example, calcein has a range of 500-550 nanometers for emission. The emission wavelength of the fluorochrome used must be sufficiently higher than the excitation wavelength of the fluorochrome.

[0029.] The greater the amount of light (lumens) striking the sample through the illuminator, the greater the detection sensitivity for fluorescence will be. It has been found that any 100-watt or greater fiber optic light source can be used in the present invention. Wattage is not the ultimate determination of the power of the detector, but what is determinative is how much light (watts, lumens, etc.) of the

proper wavelength actually strikes the sample. While light, such as produced by light bulbs, is composed of a wide range of wavelengths, the filters placed into the device allow only those specific wavelengths already present in their respective quantities to pass through.

[0030.] Any type of light may be used to excite the fluorochrome, including light from a mercury vapor lamp, a tungsten halogen, xenon, laser, or any combination of light sources.

[0031.] The preferred condition for detecting fluorescence with the device of the present invention is a completely dark environment, so that the fluorescence is most easily visible. However, certain fluorochromes, such as calcein, can be detected under low to moderate lighting as well. Also, as some fluorochromes may not be readily detected in acidic or basic environments, the particular fluorochrome used may be chosen based upon its activity in the particular environment in which it is to be used.

[0032.] In another embodiment of the present invention, the device rests on a flat surface such as a table or bench top. In addition, a fiber-optic light source can be used rather than a standard illuminator. All of the filters and lenses are similar to the device described above, except that they are all housed in a single structure known as a fluor-cluster, which is positioned at the tip of a flexible fiber optic gooseneck or light guide. This embodiment provides a larger

target area for detecting fluorescence, since a higher power light source can be used. This embodiment makes it possible to examine multiple organisms or samples simultaneously, depending upon the size of the sample. Large numbers of samples can be processed more efficiently than would be possible by examining one sample at a time.

[0033.] This alternative embodiment is shown in Figure 2. Light generated by a power supply 21 travels through a flexible light guide 22 and is directed through and processed by an exciter or bandpass filter 24. An adapter 23 facilitates attachment of the light guide 22 to a fluor-cluster housing 27. The light hits a beamsplitter 26 and is directed downwards towards the specimen 28. If the specimen contains sufficient fluorochrome, it will emit light of a slightly longer wavelength than that of the incident light. This emitted light will be reflected upwards from the specimen 28 through a beamsplitter 26 and travel towards the line of sight. Emitted light will then pass through a barrier or longpass filter 25, where only light having a wavelength longer than that of the incident light will be allowed to pass to the eye of the observer (line of sight). The presence of a fluorochrome in the specimen will cause a visible fluorescence to occur.

[0034.] Figure 4 shows a hand-held fluorochrome detector 40 including fluor-cluster filter housing 41 using a battery-operated light source (not shown). Optional filter glasses

can be used so that the operator can view a sample from any vantage point as long as the excitation light is visible.

[0035.] Figure 5 shows a cutaway view of the filter housing 50 of the fluorochrome detector of the present invention, including an achromatic lens for magnification 51, a longpass barrier filter 52, a coated beamsplitter 53, head cap screws 54 to secure the two halves of the filter housing, a bandpass exciter filter 57, and a retaining ring groove 56.

[0036.] The filter housing is interchangeable between the benchtop and hand-held fluorochrome detectors.

#### **Principles of Fluorescence Detection**

[0037.] Excitation energy is beamed from a light source through an exciter filter, a filter located between the light source and the sample to screen out undesired wavelengths of light and allow a select band of excitation radiation to pass through to the sample. Selected wavelengths of light energy which pass through an exciter filter are able to cause a sample or specimen which contains material such as a fluorochrome compound, to emit light energy of some greater wavelength value. The emitted light energy then passes through a barrier filter which blocks out unwanted background illumination allowing the observer to detect visible fluorescence.

[0038.] Also incorporated into the present invention is a dichroic beamsplitter. This is a highly efficient beamsplitter that selectively reflects virtually all of the

desirable short wavelength exciting light to the specimen, and selectively transmits the longer wavelength fluorescence emitted from the specimen for detection by the observer. The dichroic beamsplitter reflects excitation energy wavelengths up to a predetermined cutoff point. Longer wavelengths, such as those emitted by fluorescence energy, pass through the beamsplitter and are not deflected from their paths. The beamsplitter enhances but is not critical to the detection of fluorescence. It also serves to redirect all desired wavelengths of light at an angle of 90 degrees from the light source to the line of sight through the detection device to facilitate observation of fluorescence by the observer.

#### **Marking Specimens**

[0039.] While the method and apparatus of the present invention can be used for detecting fluorescence in any type of material, they are particularly useful in detecting fish which have been labeled as fry, or other animals that have been labeled and released to the wild or are subjects of experimental comparison to determine, after a period of time, which of the animals are still extant.

[0040.] One method for labeling fish fry is by immersion in a solution of a suitable fluorescent material, such as calcein. Fish can be immersed at any age, which for Atlantic salmon can be performed as early as prior to the onset of exogenous feeding, approximately 60 days post-hatch.

[0041.] In one method of labeling fish fry, solutions of 125

mg/L calcein and 250 mg/L calcein were prepared. Test jars were filled with hatchery water minus 300 mL. Two hundred larvae were placed into each jar, followed by 300 mL of one of the calcein solutions mixed to achieve the desired chemical concentrations. Single-bubble aeration was introduced via 3.2 mm diameter plastic tubing to prevent oxygen depletion during the static, 48 hour immersion. Ambient-temperature water was allowed to flow around the outside of the test jars to keep water temperatures stable. At the end of 48 hours, water quality characteristics (pH, temperature, and dissolved oxygen) were recorded and fresh flow-through water was introduced to all jars, thereby flushing the calcein solutions.

[0042.] At the onset of exogenous feeding, live brine shrimp *Artemia* sp., supplemented with a formulated dry diet, were introduced equitably into each replicate daily. As reported in Mohler, *North American Journal of Fisheries Management* 17:751-756, 1997, samples were taken from the fins of fish and samples were viewed under fluorescent microscopy.

[0043.] Gross examination of the fish at ten days postimmersion under fluorescent microscopy revealed that all fish from both calcein treatments has acquired a mark that was detected as apple-green fluorescence in visible bony structures.

[0044.] After 234 days postimmersion the calcein marks were generally retained at the point of origin. Loss of brilliance

at the distal edge of the marked area of the caudal fin suggested that some calcein diffused into developing fin ray tissue during growth. However, if the proper area is located in the sample area of the detection device, detection is reliable. Later, unpublished experiments showed that calcein can be induced into calcified tissues in as little as 7 minutes by immersing fish into hyper-osmotic solutions of saltwater (1-5% salinity) for 3.5 minutes followed immediately by a 3.5 minute bath in a concentrated calcein solution (0.5-1.0%). This technique induced a calcein mark on fin rays and bones of Atlantic salmon with greater consistency and brilliance than previously reported using a passive immersion for 24-48 hours in duration.

[0045.] The device of the present invention makes it possible to examine much larger samples than was possible with the prior art. Moreover, living macro-organisms, such as fish, can be non-lethally examined. The device of the present invention can be readily transported into harsh environmental conditions for field work, and a large number of samples can be quickly examined. The device of the present invention provides a wider field of view of detection of fluorescence than that of the prior art, and is less expensive than previously used microscopes.

[0046.] As noted above, any fluorochrome can be used in the present invention as long as the emission wavelength is sufficiently longer than the excitation wavelength to be

[0047.] The following list of fluorochromes is meant to illustrate types of fluorochromes that can be used, including their excitation and emission spectra. However, this list is for purposes of illustration only, and is not meant to be limiting.



Fluorochrome	Spectral Data	
	Excitation	Emission
Acridin yellow	470	550
Acridin organe + DNA	502	526
Acridin orange + RNA	460	526
Acriflavin-Feulgen	480	550-600
Adrenaline	-	-
Alizarin complexon	530-560	580
Allophycocyanin	630	660
AMCA	345	425
7-Amino-actinomycin D	555	655
Amino-methylcumarine	354	441
6-Amino-Quinolin	360	443
Atebrin	436	490
Auramin	460	550
Auraphosphinmin	460	550
BAO (Ruch)	280	460
BCECF	430/480	520
Berberine sulfate	430	550
BOBO-1	462	481
BOBO-3	570	602
BODIPY	503	512
BODIPY 581/591 phalloidin	584	592
Calcein	495	500-550
Calcein blue	375	420-450
Calcium Crimson	588	611
Calcium Green	506	534
Calcium Orange	554	575
Calcofluorwhite	440	500-520
Cascade blue	376/399	423
Catecholamine	410	470
Chinacrin	450-490	515
Chlorotetracycline	-	-
Chromomycin/mitramycin	436-460	470
Coriphosphin	460	575
CPM	385	471
CTC 5-cyano-2,3- ditolyl-Tetrazolium- Chlorid	602	-

Fluorochrome	Spectral Data	
	Excitation	Emission
Cyanine Cy2	489	505
Cyanine Cy3	575	605
Cyanine Cy5	640	705
Dansylamide	340	578
Dansylchloride	380	475
DAO	-	-
DAPI + DNA	359	461
DASPMI	-	-
DiBAC4 Dibutylbarbituric acid trimethine oxonol	439	516
DIDS thiocyanato-stilbene	342	418
DiI C3/4/12/22 indocarbocyanine	540-560	556-575
DiOC2/7/16 carbocyanine	550	580
DiSC1/2/3/6 thiocarbocyanine	559	585
Diaminonaptylsulfanic acid	340	525
DPH	350	452
Dopamin	340	490-520
DTAF	495	528
Ethidium bromide + DNA	510	595
Euchrysin	430	540
Evans blue	550	611
Fastblue	-	-
Feulgen	480	560
FIF-Falk	405	435
Fluo-3	480	520
FLURAM Fluorescamine	-	-
FDA Fluoresceindiacetate	499	-
FITC Fluorescein-isothiocyanate	490	525
Fluorogold	350-395	530-600
Blue FluoSpheres	360	415
Crimson FluoSpheres	625	645
Red FluoSpheres	580	605
Dark Ref FluoSpheres	650	690
Yello-Green FluoSpheres	490	515
FURA-2	340/380	500/530

	Spectral Data	
Fluorochrome	Excitation	Emission
Generic blue/green combination	-	-
GFP blue (Green Fluoresc. Protein)	382	448
GFP green	471	503
GFP Mutant W	458	480
GFP Wild Type	396	508
Haematoporphyrin	530-560	580
Hoechst 33258 (Bisbenzimid)	365	480
Hoechst 33342 (Bisbenzimid)	355	465
ImaGene Green substrates	-	-
ImaGene Red substrates	-	-
Indo-1	360	410/480
Life/Dead Viability/Cytotoxicity Kit	-	-
Lissamin-Rodamin B	535	580
Lucifer Yellow	428	540
Magdal red	540	570
Mepacrin	-	-
Merocyanine	555	578
MEQ, methoxy-ethylquinolinium	344	442
4-Methylumbelliferon	360	450
Methyl green/pyronin stilbene	-	-
Mithramycin	420	575
NBD-Amine	460-485	534-542
NBD - chloride	480	510-545
Nile redt	485	525
Noradrenaline	340	490-520
Olivomycin	350-480	470-630
Oxytetracyclin	-	-
Pararosaniline-Feulgen	560	625
PBFI	340/380	420
Phosphine	465	565
C-Phycocyanine	605	645
R-Phycocyanine	-	-
B-Phycoerythrine	546/565	575

T0100034360

Fluorochrome	Spectral Data	
	Excitation	Emission
R-Phycoerythrine	480-550	578
PKH 26 (Sigma)	551	567
POPO-1	434	456
POPO-3	534	570
Primulin	410	550
Propidium iodide	536	617
Pyren	343	380-400
Pyrolidin-Methyltetra- cycline	-	-
Pyronin	490-580	530-610
QUIN 2	340/365	490
Quinacrine mustard	440	510
Resorufin	571	585
Rhodamine	540-560	580
Rhodamine 123	540-560	580
Rhodamin Phalloidin	550	575
Rhodol green	500	525
Acid fuchsine	540	630
SBFI	340/380	420
Serotonin	365	520-540
SNARF	480	600/650
Stilbene SITS, SITA	365	460
Sulfaflavin	380-470	470-580
Tetracycline	390	560
Tetramethylrhodamin	540	566
Texas red	595	620
Thioflavin	430	550
Thiazin red	510	580
TMA-DPH	355	430
TOTO-1 + DNA	509	533
TOTO-3 + DNA	642	661
TRITC	540	580
XRITC	560	620
YOYO-1	491	509
YOYO-3	642	660
Xylenol orange	377	610
Immunogold, Silver	-	-

[0048.] The foregoing description of the specific embodiments will so fully reveal the general nature of the invention that others can, by applying current knowledge, readily modify and/or adapt for various applications such specific embodiments without undue experimentation and without departing from the generic concept, and, therefore, such adaptations and modifications should and are intended to be comprehended within the meaning and range of equivalents of the disclosed embodiments. It is to be understood that the phraseology or terminology employed herein is for the purpose of description and not of limitation. The means, materials, and steps for carrying out various disclosed functions may take a variety of alternative forms without departing from the invention.

[0049.] Thus, the expressions "means to..." and "means for ...", or any method step language, as may be found in the specification above and/or in the claims below, followed by a functional statement, are intended to define and cover whatever structural, physical, chemical, or electrical element or structure, or whatever method step, which may now or in the future exist which carries out the recited functions, whether or not precisely equivalent to the embodiment or embodiments disclosed in the specification above, *i.e.*, other means or steps for carrying out the same function can be used; and it is intended that such expressions be given their broadest interpretation.

## REFERENCES

Diehl, H., et al., 1956. Indicator for titration of calcium in presence of magnesium using disodium dihydrogen ethylenediamine tetraacetate. *Analytical Chemistry*. 28:882-884.

Mohler. 1997. *North American Journal of Fisheries Management* 17:751-756.

Muncy, R.J., et al. 1990. Inorganic chemical marks induced in fish. Pages 541-546 in N.C. Parker and five coeditors, *Fish-marking techniques, American Fisheries Society, Symposium 7*, Bethesda, Maryland.

Oncel, M., et al. 1990. Calcein angiography: a preliminary report on an experimental dye. *International Ophthalmology* 14: 245-250.

Refojo, M.F., et al. 1972. A new stain for soft hydrophilic lens fitting. *Archives of Ophthalmology*. 87:275-277.

Wallach, D.F.H., et al. 1959. Preparation and properties of 3,6-dihydroxy-2,4-bis-[N,N'-di(carboxymethyl)-aminomethyl]fluoran. Utilization for the ultramicrodetermination of calcium. *Analytical Chemistry* 31:456-460.

Wilson, C.A., et al. 1987. Calcein as a fluorescent marker of otoliths of larval and juvenile fish. *Transactions of the American Fisheries Society* 116:668-670.